



Linear LED High Bay

High bay fixtures for general interior lighting applications. Ideal for commercial buildings, factories, warehouses, supermarkets, etc.

Our products feature high quality components from industry leading manufacturers for superior performance and longevity.

Photometric studies and analysis show that the performance of our 160W LED high bay fixture far exceeds the illumination from a 400W metal halide HID high bay...using only 30% of the energy. While our 110W version outperforms the illumination of a 6 tube T8 fluorescent high bay...using less than half the energy!

We carry a complete line of products to meet all types of commercial needs. Our products are engineered to install very simply and make the transition from HID or fluorescent lighting very cost-effective.

100,000 hrs rated life

10 Year Warranty



◆ FEATURES

- Reduce energy consumption and operating costs by 70% or more
- Maintenance free operation - lasts up to 10 to 20 times longer than conventional lighting
- No UV or IR and no RF interference
- Suitable for damp locations and can be surface mounted or suspended for maximum flexibility in numerous applications.
- Environmentally friendly - fully recyclable, no mercury or other hazardous material
- Listed on the DLC Qualified Products List



for more information email info@emium.com

or call 224.735.3435 | www.emium.com



emium

emium lighting, see differently


SPECIFICATIONS

| | | | | | |
|------------------------------------|---|---------------|---------------|---------------|-----|
| Model | EL-ZY-H2-110W | EL-ZY-H5-160W | EL-ZY-H3-220W | EL-ZY-H6-320W | |
| Power (watts) | 110 | 160 | 220 | 320 | |
| Lumen Output | 13,700 | 19,200 | 26,700 | 39,300 | |
| Efficacy | > 120 lm/watt | | | | |
| Input Voltage | 100-277VAC or 480VAC | | | | |
| CRI | > 80 R _a | | | | |
| Color | 5600K | | | | |
| Dimensions | Length | 24" | 24" | 46" | 46" |
| | Width | 12.6" | 18" | 12.6" | 18" |
| | Height | 4" | 4" | 4" | 4" |
| Diffuser/cover | Frosted or no cover, optional wire guard (glass free) | | | | |
| Operating Temperature | -30°F to 140°F | | | | |
| Mounting Options | Surface mount Cable or chain suspension (with v-clips for dual point) Pendant mount | | | | |
| Suitable for damp locations | Yes | | | | |
| Dimmable | Yes 0 - 10V (optional) | | | | |
| Rated Life | 100,000 hrs | | | | |

Pendant mount



Suspension mount



for more information email info@emium.com
 or call 224.735.3435 | www.emium.com


emium
emium lighting, see differently