



---

**BLG-LEDBLT-HGL-X24I-XEMG LED Blasting Gun Light**

**Lamp Type:** LED

**Dimensions:** 4.75"-L 3"-W - 10"-H

**Weight:** -

**Voltage:** 120-277V AC 50/60 Hz stepped down to 24V DC

**Total Watts:** 18

**Total Lumens:** 1530

**Luminous Efficacy:** 85 Lm/W

**Lamp Life Expectancy:** 50,000 Hours

**Light Color:** 5,000K

**CRI:** 85

**Beam Type:** 25° Spot or 60° Flood

**Amps:** 0.15A @ 120V, 0.075A @ 240V, 0.065A @ 277V, 1.5A @ 12V, 0.75A @ 24V

**Housing Materials:** Cast Aluminum

**Quick Swap Lens Materials:** 3 Glass (Metal) or 3 Polycarbonate (Garnet)

**Temp Range:** -40°C to +85°C

**Typical Case Temperature:** ~20°C above ambient temperature

**Mounting:** Clamp on Blasting Gun Mount

**Wiring:** 100' 12/3 SOOW cord, inline transformer, 5' 16/3 SOOW

**Cord Cap:** 5-15, 6-15, 5-20, 6-20, L5-15, L6-15, L5-20, L6-20, BS1363, Schuko, or Pigtail

**Battery Runtime:** 90 Mins

**\*Blasting Gun Not Included**

**Ratings/Approvals**

IP65 Ingress Protection

Polycarbonate Handle for Increased Handling

Quick-Change Lens - Swap w/ Gloves On

Glass or Polycarbonate Lenses

120-277V AC Universal Voltage

Multiple Plug Options

External Battery Backup

**Special Orders- Requirements**

Contact us for special requirements

**Toll Free: 1-800-369-6671**

**Intl: 1-903-270-1187**

**E-mail: [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)**

**Options:**

**-Beam Config-Lens-Cord Cap**

**Example: -SP-GLASS-5.15**

Beam Config	
SPOT	-SP
FLOOD	-FL

Lens	
GLASS	-GLASS
POLYCARBON ATE	-PC

Cord Cap	
5-15 STRAIGHT	-5.15
6-15 STRAIGHT	-6.15
L5-15 TWIST	-L5.15
L6-15 TWIST	-L6.15
UK BS1363	-BS1363
INTL SCHUKO	-SCHUKO
PIGTAIL	-PIGTAIL

Links (Click on the below items to view):

- [Addpic1large](#)
- [Addpic2large](#)
- [Addpic3large](#)
- [Addpic4large](#)
- [large](#)
- [medium](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [HigResPic9](#)
- [HigResPic10](#)