

Portable Explosion Proof Receptacle - C1D2, C2D1&2 - 480V - 63 Amps - 3-pole, 4-wire - IP66

Part #: HLC-EX-63A-3P4W-480V.3P



The Larson Electronics HLC-EX-63A-3P4W-480V.3P Portable Explosion Proof Receptacle is recommended for use in Class I, Division 2; Class I, Zones 1 & 2; Class II, Divisions 1 & 2; and Class III work sites. This 30-amp rated outlet comes in a 3-pole, 4-wire configuration with 480V AC compatibility. Constructed of fiberglass reinforced polyester, the NEMA-rated unit features IP66 protection. The HLC-EX-63A-3P4W-480V.3P is a portable unit with a back plate and a cgb connector included for customer provided cords.

The HLC-EX-63A-3P4W-480V.3P is designed for secure electrical connections in hazardous locations. This 3-pole, 4-wire receptacle is rated at 63 amps and is compatible with 480V AC. The NEMA-rated unit features non-metallic, fiber reinforced polyester construction and IP66-rated protection. Specially designed color coding and pin configuration reduces the possibility of making incorrect power connections. Seals are not required when this explosion proof receptacle is used for Class I, Division 2 applications. A 1.5" NPT hub is available at the bottom of the outlet. This receptacle is compatible with our HLP-EX-63A-3P4W-480V.3P hazardous plug. This portable receptacle comes with a back plate and cgb for connection to operator provided wiring.

Applications: Manufacturing, industrial, warehouse, lighting, motor-generator sets, compressors, wet areas or locations where combustible dusts, fibers or flying are present or where explosive gases or vapors may be present.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Specifications / Additional Information

<u>HLC-EX-63A-3P4W-480V.3P Portable Explosion Proof Receptacle</u>	<u>Ratings/Approvals</u>
Unit Type: Explosion Proof Receptacle	Class I, Division 2 Groups A,B,C,D
Dimensions: 16"H x 7.1"W x 8.3"D	Class I, Zones 1 & 2 Ex de IIC T
Weight: 18lbs	Class II, Divisions 1 & 2 Groups E,F,G
Voltage: 480V AC	Class III
Amps: 63	NEMA 3,3R,4X
HP (3 Phase): 40HP @ 480V AC	IP66
Configuration: 3-pole, 4-wire	PTB 01 ATEX 1150
Hubs: (1) 1.5" NPT Hub	
Receptacle Mounting: (3) 5/16" Bolts, Back Plate w/ CGB	
Ambient Operating Temp: -50°C - +55°C	<u>Special Orders- Requirements</u>
Materials: Fiberglass Reinforced polyester	Contact us for special requirements
Terminal Capacity: 2/0 AWG (115A)	Toll Free: 1-800-369-6671
Compatibility: HLP-EX-30A-3P4W-480V.3P Plug	Fax: 1-903-498-3364
	E-mail: sales@larsonelectronics.com

[Scroll Down to Purchase-](#)

[This product does not qualify for free shipping.](#)

[Part #: HLC-EX-63A-3P4W-480V.3P \(152432\)](#)

Links (Click on the below items to view):

- [Hi-Res Image 1- Explosion Proof Receptacle](#)