

## Explosion Proof Network IP Camera w/ Built-in LED - 2.0MP, 30FPS - PoE + 12/24V DC - 108° FOV

**EXPCMR-IP-POEP-2MP-108D-1XLE3-1224**



### EXPCMR-IP-POEP-2MP-108D-1XLE3-1224 Network Explosion Proof Camera

**Listing:** United States and Canada

**Dimensions:** -

**Weight:** -

**Camera Watts:** 5W (Max)

**LED Light Watts:** 12W

**Camera Power Source:** PoE (802.3af)

**LED Light Voltage:** 12V DC or 24V DC

**Image Sensor:** 1/2.5" Progressive Scan CMOS sensor

**Signal System:** NTSC

**Video Resolution:** 2.0MP (1920x1080)

**Frame Rate:** Up to 30fps @ 1920x1080 resolution

**Compression Type:** H.265+, H.265, H.264 OVC, H.264, MJPEG

**Bit Rate:** 32Kbps - 16Mbps

**Focal Length:** 2.8mm

**Max Field of View:** 108°

**Shutter Speed:** 1/3s to 1/10,000s

**Day/Night:** True D/N w/ Mechanical Cut Filter

**Min. Illumination:** 0.01 lux (Color) / 0 lux (w/ Built-in IR)

**Lumens:** 720 lumens

**LED Color Temp Options:** 6000K or 3000K

**LED Beam Pattern:** Flood or Spot

**LED Spot Beam:** 120`L x 60`W

**LED Flood Beam:** 80`L x 80`W

**Digital Noise Reduction:** 3D DNR

**Ethernet Interface:** RJ45

**Ethernet Speed:** 10/100

**Protocols:** TCP/IP, HTTP, HTTPS, DHCP, UDP, RTP, RTSP and more

**Remote Configuration:** Yes

**Ambient Temperature Range:** -22°F to +140°F

**Housing Materials:** Copper-free Aluminum Alloy

**Lens Material:** 3/8" Thick Tempered Glass

**Mounting:** Adjustable rear-mounted handle/bracket

**Wiring Hub:** (2) 3/4" NPT

### Quick Summary

Class I, Divisions 1&2 Groups B, C, D

Class I, Zones 1&2 Groups IIB+H2, IIA

Class II, Divisions 1&2 Groups E, F, G

Class III

Ex db IIC Gb

Ex tb IIC Gb Db IP66

NEMA 3, 4, 4X, 7 (B, C, D), 9 (E, F, G)

Main stream and two sub streams

Capable of programming unique settings per stream

ONVIF Profile S Certified

WDR (wide dynamic range) for auto adjusting

### Special Orders/Requirements

Contact us for special requirements

**Phone:** 1-903-498-3363

**Toll Free:** 1-800-369-6671

**Fax:** 1-903-498-3364

**E-mail:** [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

**The EXPCMR-IP-POEP-2MP-108D-1XLE3-1224 Network Explosion Proof Camera w/ Built-in LED Light from Larson Electronics is a remote inspection camera specifically designed for observation in hazardous**

**locations. This explosion proof, dust/ignition proof, weather proof and tamper resistant camera provides the operator with a live feed from inside tanks, reactors, vessels or other hazardous locations. Operated remotely from a centralized control room, this remote inspection camera saves both time and money as well as contributing to workplace safety.**

**Camera Features:** The EXPCMR-IP-POEP-2MP-108D-1XLE3-1224 Network Explosion Proof Camera features a built-in 1/2.5" progressive-scan CMOS image sensor that delivers up to 2.0MP resolution at 30 fps. The wide angle fixed lens with 108° field of view is designed to cover large areas and work spaces. This explosion proof camera provides a crisp and clear image for everything within the 108° focal area. Total distance is dependent on mounting height and angle. The unit comes with built-in LED lights to support image capturing in low-light conditions and after sunset. This component is available in two lighting configurations: spot or flood. Four CREE EZBright® three watt LEDs producing 180 lumens, for a total of 720 lumens, each are arranged in rows and paired with high purity 10 degree optics to produce a tightly focused spot beam with limited spread or light spillage. The spot configuration features a 10° beam that measures 120`L x 60`W. The explosion proof LED light is powered using a customer-provided 12V DC or 24V DC low voltage power source, while the explosion proof camera is powered by PoE.

This remote inspection camera utilizes 120dB true Wide Dynamic Range, 3D Digital Noise Reduction and a true day/night IR-Cut Filter Removal to produce clear images in variable and low light conditions. The camera LED is available in 3000K or 6000K color temperature.

**Wiring:** Link-up with the camera is achieved via a customer provided RJ45 Ethernet cable which is ran back to the customer provided DVR system mounted outside the hazardous location. Camera power is delivered via the same Ethernet cable using Power over Ethernet (PoE) technology. This not only increases flexibility in deployment, but also provides time and cost savings as well. Our explosion proof cameras with Power over Ethernet (PoE) features enable data transfers and power to be passed through a single Ethernet cable that is usually a Cat 3/Cat 5 cable or better. There are several types of PoE, which come with their own respective standard and maximum power to port capabilities. The IEEE 802.3af PoE standard, with a voltage range of 44.0 - 57.0V, offers 15.4W of DC power for each port. The IEEE 802.3at PoE standard, with a voltage range of 50.0 - 57.0V, provides up to 30W of DC power per port, which is ideal for surveillance cameras, antennas and network access points. The IEEE 802.3bt PoE standard, with a voltage range of 50.0 - 57.0V, provides 60W of DC power for each port. In order to utilize PoE properly, the components, such as the receiving unit and sending device, must be PoE compliant.

**Recording:** To record the stream from this camera, a NVR (network video recorder) is required. Larson Electronics provides a line of explosion proof, hazardous location, and non-classified NVR`s to work in conjunction with this explosion proof camera. This camera is live-view capable without any NVR system via remote access to the camera. Three streams are available, one main stream for recording and two sub streams for live viewing or additional resources. Each stream can be configured to different resolutions and frame rates.

**Mounting:** The EXPCMR-IP-POEP-2MP-108D-1XLE3-1224 Network Explosion Proof Camera features an ATEX/IECEx certified copper-free aluminum alloy body. The camera and LED light includes an adjustable rear-mounted polished stainless steel mounting bracket/handle. Additional accessory pole mounts and magnetic mounts are available separately.

**Applications:** Vessel, tank and reactor monitoring, remote observation of external facilities, monitoring of cleaning, spray patterns, mixing, foaming, reaction and level.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the

Larson Electronics LLC  
9419 E US HWY 175, Kemp, TX 75143  
Phone: 800.369.6671



[www.LarsonElectronics.com](http://www.LarsonElectronics.com)  
Email: [sales@LarsonElectronics.com](mailto:sales@LarsonElectronics.com)  
Fax: 903.498.3364

---

lighting and electronics business since 1973. Contact us today at 800-369-6671 or message [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com) for more information about our custom options tailored to meet your specific industry needs.

---

**Options:**

**EXPCMR-IP-POEP-2MP-108D-1XLE3-1224-Beam Config-Color Temperature-LED Voltage**

**Example: EXPCMR-IP-POEP-2MP-108D-1XLE3-1224-FL-FL-12V**

Beam Config	
FLOOD	-FL
SPOT	-SP

Color Temperature	
6000K	-FL
3000K	-SP

LED Voltage	
12V DC	-12V
24V DC	-24V

Links (Click on the below items to view):

- [large](#)
- [medium](#)
- [SpecSheet](#)
- [HigResPic1](#)