

Hazardous Location Breaker - Class I, Zone 1/Division 2 - 277V AC/250V DC Max - 20A - Panel Mount

Part #: [HLX-SWG-EB-277V-1P-20A](#)



The Larson Electronics HLX-SWG-EB-277V-1P-20A Hazardous Location Breaker ensures electrical safety inside combustible facilities. This 1-pole unit offers 10 kAIC breaking capacity and compatibility with 277V AC (max) and 250V DC (max). The 20-amp rated breaker provides flameproof, thermal magnetic protection.

The HLX-SWG-EB-277V-1P-20A offers reliable circuit protection for equipment used in flammable work sites. Equipped with a 10 kAIC breaking capacity, the unit is compatible with 277V AC (maximum) and 250V DC (maximum). This 1-pole hazardous location breaker carries a 20-amp rating with flameproof, thermal magnetic branch circuit protection.

This circuit breaker is suitable for use in Class I, Division 2 and Class I, Zone 1 rated hazardous locations. Wiring connections are facilitated by terminals on the unit. Operators can mount the circuit breaker inside panels or to backplates inside enclosures.

Applications: Hazardous locations, circuit protection, power distribution, electrical safety and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Specifications / Additional Information

HLX-SWG-EB-277V-1P-20A Hazardous Location Breaker

Listing: United States, Canada

Unit Type: Hazardous Location Circuit Breaker

Dimensions: -

Weight: -

Voltage: 277V AC Max, 250V DC Max

Amps: 20A (Rated @ Ta = 25°C)

Poles: 1P

Capacity: 10 kAIC

Method of Protection: Flameproof w/ Thermal Magnetic Branch Circuit Protection

Materials: -

Mount: Panel/Backplate Mount

Wiring: Terminals

Ratings

Class I, Division 2 Groups A,B,C,D

Class I, Zone 1 AEx de IIC T5 or T6

Ex de IIC T5 or T6

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: +01-903-498-3364

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

[Scroll Down to Purchase-](#)

[This product does not qualify for free shipping.](#)

[Part #: HLX-SWG-EB-277V-1P-20A \(224484\)](#)

Links (Click on the below items to view):

- [Hi-Res Image 1- Hazardous Location Breaker](#)