

LLP-JD-TR-LEDEQ-HiLo LED Tractor Light Package

Quick Summary

Buy American Compliant

The LLP-JD-TR-LEDEQ-HiLo LED Tractor Light Package comes with 4 LEDEQ-3X2-CPR LED Work Lights. Two of the light heads come with a Flood Beam configuration for use as front grill flood headlamps and the other two come with a spot beam configuration for use as front grill high beam spot lights. The LLP-JD-TR-LEDEQ-HiLo LED Light Package is ideal for installation and use on most John Deere Tractor front grills. Each LEDEQ-3X2-CPR produces 2,100 lumens of high-intensity LED light output with low voltage and amp draw, a 50,000 hour rated service life and 9 to 42 volt compatibility that provides operators with a versatile and powerful LED tractor lighting solution.

LEDEQ-3X2-CPR: This LED light bar is capable of emitting up to 2,100 lumens during operation. The 30-watt fixture features 9-64V DC input voltages and an electric current of 2.8 A. During output, the luminary shines a brilliant white light with a color temperature of 6000K. The fixture is capable of withstanding rough treatment and immersions up to 3.3 feet (IP67).

The LEDEQ-3X2-CPR light's housing is made up of aluminum, while the lens is constructed of polycarbonate. This unit complies with CE, ROHS and E4 standards. It is IP67 certified, which provides complete protection from dust and water immersions up to 3.3 feet. This lamp uses Cree® LED units that have been chosen for their high lumen per watt ratio and extreme longevity. These Cree® LEDs generate a high lumens-per-watt ratio, effective lumen output and supports 70 percent lumen retention at 50,000 hours, giving them better efficiency and operational life than traditional light sources.

LEDEQ-3X2-CPR Mounting: It is mounted using a U-bracket style trunnion mount, making vertical light direction adjustments easy to implement. **LED Benefits:** Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life. LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the

Larson Electronics LLC 9419 E US HWY 175, Kemp, TX 75143 Phone: 800.369.6671



www.LarsonElectronics.com Email: sales@LarsonElectronics.com Fax: 903.498.3364

glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Mounting: The LED lights in this cab light upgrade kit mount in existing lamp holders for halogen lamps on most John Deere tractors. This means that this LED cab light upgrade kit is easy to install without any major modifications to the cab or body of the tractor.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



www.LarsonElectronics.com Email: sales@LarsonElectronics.com Fax: 903.498.3364

Links (Click on the below items to view):

- Addpic1large
- large
- medium
- SpecSheetSpanish
- HigResPic1
- HigResPic2