

***RENT* 36" Explosion Proof High Velocity Fan - 14850 CFM - 1-1/2 HP - C1D1/C2D1 - 50' Cord**

Part #: [RNT-EPF-HSPF-36-1.5HP-50](#)



Made in the USA**This unit is for rentals**

The Larson Electronics explosion proof fan is a high pressure, high volume unit that can be used to support active ventilation in hazardous work locations. This robust industrial fan is capable of circulating air at a rate of 14,850 cubic feet per minute (CFM). When it comes to explosion proof ratings, the machine may be used in facilities that handle Class I, Group D combustible substances, such as acetone, butane, gasoline and methanol; as well as Class II, Group F & G ignitable compounds, including coal, charcoal, flour, grain and wood.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO THIS PRODUCT

Features: This hazardous area unit features a non-sparking cast aluminum propeller with a 36-inch diameter. It offers compatibility with 115/230V 60 Hz voltages. Under the hood, the machine is powered by a 1.5 HP, fully enclosed explosion proof motor. This allows the blade to rotate up to 1,725 times per minute (RPM) at a rate of 14,850 CFM. During operation, the unit emits 88 decibels from a distance of 10 feet, which is equivalent to the sound of busy city traffic.

[Click Photos to Enlarge](#)



5-15 Straight Blade Plug



5-20 Straight Blade Plug



6-20 Straight Blade Plug

The single phase explosion proof fan supports the following cord cap options: 5-15P, 5-20P and 6-20P. This unit weighs approximately 415 pounds and is compatible with portable and stationary mounting preferences. The high stand model features a 360-degree tilt, which offers superior flexibility during setup. This fan comes with a 50-foot 16/3 SOOW cable, making it suitable for use in demanding indoor and outdoor industrial environments due to its resistance to oil, abrasion and moisture.

Applications: Class I, Group D and Class II, Group F & G hazardous areas that require ventilation, including (but not limited to) the following: clean rooms, marijuana extraction rooms, laboratory hoods, oil refineries, grain mills, chemical plants, welding shops, chemical storage areas and battery changing areas.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Made in USA Quality

Specifications / Additional Information

RNT-EPF-HSPF-36-1.5HP-50 - 36" Explosion Proof High Velocity Fan - 14850 CFM

Type: Explosion Proof Industrial Fan

Propeller Dimensions: 36" Diameter

Propeller Material: Non-Sparking Cast Aluminum

Weight: 415 lbs

Voltage: 115/230V 60 Hz

Motor: 1.5 HP Fully Enclosed Explosion Proof

Rotations Per Minute (RPM): 1,725

Peak CFM: 14,850

Decibels @ 10': 88

Mounting: Portable or Stationary Mount

Wiring: 50' 16/3 SOOW Cable

Cord Cap: 5-15P, 5-20P, 6-20P - Explosion Proof

Warranty: Yes - 1 Year*

Quick Summary

Class I, Divisions 1 & 2, Group D

Class II, Divisions 1 & 2, Group F & G

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-498-3363

E-mail: sales@larsonelectronics.com

[Scroll Down to Purchase-](#)

[This product does not qualify for free shipping.](#)

[Part #: RNT-EPF-HSPF-36-1.5HP-50 \(224457\)](#)

Links (Click on the below items to view):

- [Hi Res Image 1](#)